

# Material Safety Data Sheet

Section 1:	Identification of Product & Supplier
<b>Product:</b>	<b>Megapoxy HICB - Part B</b> (Use in conjunction with Megapoxy HICB - Part A)
<b>Classification:</b>	<b>Hazardous according to criteria of Worksafe Australia</b>
<b>Uses:</b>	Liquid epoxy grout for grouting machinery, backing crusher parts
<b>Supplier:</b>	<b>Crushing &amp; Mining Equipment Pty Ltd</b>
<b>ABN:</b>	<b>33 009 300 690</b>
<b>Street Address:</b>	<b>Cnr Lee Rd and Macedonia St</b> <b>Naval Base, WA 6165, Australia</b>
<b>Telephone:</b>	<b>61 8 9437 1477</b>
<b>Facsimile:</b>	<b>61 8 9437 1577</b>
<b>Emergency Phone:</b>	<b>As Above or After Hours 61 2 9484 7958 or 0418 112 515</b>
<b>email:</b>	<a href="mailto:sales@crushingandmining.com">sales@crushingandmining.com</a>

Section 2:	Hazards Identification
<b>Hazard Category:</b>	Xn Harmful, Xi Irritant
<b>Risk Phrases:</b>	R21/22/34 Harmful in contact with skin and if swallowed. Causes t R43 May cause sensitisation by skin contact.
<b>D.G. Class:</b>	8
<b>Subsidiary Risk:</b>	Nil
<b>Poison Schedule:</b>	S 5
	This product is a Schedule Poison S 5 and must be stored, maintained & and used in accordance with the relevant regulation.

Section 3:	Composition & Information on ingredients												
<b>Ingredients:</b>	<table><thead><tr><th>Name</th><th>Cas No.</th><th>Proportion</th></tr></thead><tbody><tr><td>Reacted ethyleneamines</td><td>112-24-3</td><td>Very High</td></tr><tr><td>Phthalocyanine Direct Dye</td><td>1330-38-7</td><td>Very Low</td></tr><tr><td>Other ingredients determined not to be hazardous</td><td></td><td>To 100 %</td></tr></tbody></table>	Name	Cas No.	Proportion	Reacted ethyleneamines	112-24-3	Very High	Phthalocyanine Direct Dye	1330-38-7	Very Low	Other ingredients determined not to be hazardous		To 100 %
Name	Cas No.	Proportion											
Reacted ethyleneamines	112-24-3	Very High											
Phthalocyanine Direct Dye	1330-38-7	Very Low											
Other ingredients determined not to be hazardous		To 100 %											
	<b>V.High &gt;60, High 30 - 60, Med 10 - 29, Low 1 - 9, V.Low &lt;1</b>												
	All the constituents of this product are listed on the Australian Inventory of Chemical Substances (AICS) and National Registration Authority (NRA) approved active constituents.												

Section 4:	First Aid Measures
	Poison Information Centres in each State capital can provide additional

assistance for scheduled poisons. (Phone Australia 131 126)

### Megapoxy HICB - Part

**Ingestion:** If swallowed do not induce vomiting. Rinse mouth with water, give glass water and seek medical attention.

**Eye contact:** Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.

**Skin contact:** Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical attention.

**Inhalation:** Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

**Note to Physician:** Treat the patient symptomatically.

<b>Section 5:</b>	<b>Fire Fighting Measures</b>
-------------------	-------------------------------

**Extinguishing media:** Water, Foam, Dry chemical powder, Carbon dioxide.

**Specific Hazards:** The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide, oxides of nitrogen, volatile amines and ammonia. Wear full protective clothing.

**Fire Fighters:** Wear positive pressure, self-contained breathing apparatus and full protective clothing.

<b>Section 6:</b>	<b>Accidental Release Measures</b>
-------------------	------------------------------------

**Small Spills:** Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soot, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.

**Large Spills:** Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soot, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crop waterways, drains or sewerage has occurred, advise Emergency Services. State Department of Agriculture.

<b>Section 7:</b>	<b>Handling and Storage</b>
-------------------	-----------------------------

**Storage:** Store in the closed, original container in a cool ventilated area. Keep

containers tightly closed when not in use. Keep away from explosives, flammable oxidising agents and organic peroxides. This product is a Scheduled Poison Class S5 and must be stored, maintained and used in accordance with the relevant regulations. Avoid from physical damage.

**Megapoxy HICB - Part**

<b>Section 8:</b>	<b>Exposure Controls &amp; Personal Protection</b>
-------------------	--

**Exposure Limits:** No value assigned for this specific product by the National Occupational Safety Commission (Worksafe Australia). However, supplier recommends the following Hygiene Standard as under;

**TWA STEL Carcinogen Notices**

Material	TWA		STEL	
	ppm	mg/m3	ppm	mg/m3
Ethyleneamines	1	6	N/E*	N/E*
Pthalocyanine Dye	N/E	10	N/E*	N/E*

**N/E\* - No Exposure Standard has been established for this product**

**Eng. Controls:** Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.

**Personal Protection:** Use overalls, safety shoes, safety goggles, rubber or chemical resistant gloves and respirator if required.

**Manufacturing:** Avoid skin and eye contact and the inhalation of vapour. Wear overalls, safety goggles and impervious gloves. Available information suggests that the product

**Packaging & Transport:** made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final assessment

**Transport:** should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716. Always wash hands with soap and water before smoking, eating, drinking or using toilet facilities.

**Preparations & use of product:** Repeated exposure may cause allergic disorders. Sensitive workers should use protective clothing. Avoid contact with eyes and skin. Do not inhale dust or vapours. After each day's use, wash gloves, safety goggles and all the contaminated clothing.

<b>Section 9:</b>	<b>Physical &amp; Chemical Properties</b>
-------------------	---

**Appearance** : Blue liquid  
**Solubility** : Soluble in water  
**Specific Gravity @ 25 deg. C** 0.98 - 1.02  
**Boiling Point (o C )** 277

**Megapoxy HICB - Part**

**Rel.Vapour Density (air=1)** : 5  
**Melting Range** : Not established  
**Vapour Pressure (20o C )** : Less than 0.01 Pa  
**Decomposition Temp.(o C )** : More than 200 deg. C  
**Flash Point (o C )** : 149  
**Flammability Limits (%)** : Not established  
**Ph** : Not applicable  
**Autoignition Temp. (o C )** : Not available  
**% Volatile by Volume** : Nil

(All above values are Typical Values only)

<b>Section 10:</b>	<b>Stability &amp; Reactivity</b>
--------------------	-----------------------------------

**Stability:** The product is stable under normal conditions and use.

<b>Section 11:</b>	<b>Toxicological Information</b>
--------------------	----------------------------------

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptom that may arise if the product is mishandled are:

**Acute Effects: Ingestion:** Harmfull if swallowed. May cause gastrointestinal discomfort irritation.

**Eye:** Brief contact may cause mild irritation to eyes.

**Skin:** Mild irritant and poorly absorbed through the skin. Prolonged repeated contact may cause severe irritation and/or dermatitis.

**Inhaled:** Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

**Long Term Effects:** Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms. Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.

**Acute & Chronic** Negative in a battery of mutagenicity assays.

**Toxicity:** No evidence of carcinogenicity was observed in long term studies of rats

No developmental nor reproductive effects in rat and rabbit.

Acceptable Daily Intake ( ADI ) for humans is 0.01 mg/kg/day.

<b>Section 12:</b>	<b>Ecological Information</b>
--------------------	-------------------------------

Avoid contamination of drains, sewerage, creeks and waterways.

**Megapoxy HICB - Part**

Product may be toxic to some aquatic organisms.

<b>Section 13:</b>	<b>Disposal Consideration</b>
--------------------	-------------------------------

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

<b>Section 14:</b>	<b>Transport Information</b>
--------------------	------------------------------

<b>UN. No.</b>	:	2259
<b>Shipping Name</b>	:	Triethylenetetramine
<b>Class</b>	:	8
<b>Subsidiary Risk</b>	:	Nil
<b>Packaging Group</b>	:	II
<b>Hazchem Code</b>	:	2R
<b>EPG</b>	:	8A1
<b>Segregation</b>	:	Not to be loaded with explosives, oxidizing agents or organic peroxides.

For road, marine and air transport this product is classified as dangerous goods within the context of National and International Transport Regulations.

<b>Section 15:</b>	<b>Regulatory Information</b>
--------------------	-------------------------------

The National Model Regulations for the Control of Workplace Hazardous Substances [ NOHSC : 10005 (1999)].

The National Standard for the Storage and Handling of Workplace Dangerous Goods [ NOHSC : 1015 (2001)].

<b>Section 16:</b>	<b>Other information</b>
--------------------	--------------------------

<b>Date of Preparation</b>	:	01.07.02
<b>Date of Revision</b>	:	01.07.07

**Reasons for Issue** : Five yearly update & new format.  
MSDS's are updated frequently. Please ensure you have the current co

This MSDS summarises at the date of issue our best knowledge of health and safety hazard information of the product, and in particular how to handle and use the product in the workplace. Since Crushing & Mining Equipment cannot anticipate or control the conditions under which the product may be used each user must, prior to usage, review this MSDS in the context to the storage and handling of the product in the workplace.

**Megapoxy HICB - Part**

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact Crushing & Mining Equipment. Our responsibility for the product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

**Approved By: Frank Taylor**

[Redacted]

, etc

[Redacted]

urns.

and

[Redacted]

i

of

)

[Redacted]

t B

s of

ites.

n

rtificial



on

n

tective



rent

oil,

rs

rent

oil,

rs

ps,

ses or




ood,  
ison

t **B**



il and  
ded



t.

ə

ated  
itration

æ

safety  
gloves  
e to  
:nt  
ur  
sh  
let

ould  
mist  
ie



t B



ns

rt and

d and

is

d at

ise

e

toms.

ing

s.



t B



t  
nd



xidising

is  
tion.



is

gerous



opy.

lth  
andle  
ent  
r be  
use

t **B**  
iate

s and

